



Model	Internal Diameter	Heated Area	A1	A2	A3	A4	A5	A6
	mm	m ²	mm	mm	mm	mm	mm	mm
P 85/15	85	0,15	1730	n.a.	n.a.	250	350	1500
P 100/3	100	0,30	2050	n.a.	n.a.	280	400	2000
M 200/7.5	200	0,75	3100	1385	1715	500	550	3020
M 250/1.3	250	1,30	3790	1520	2270	520	600	4010
M 320/2.3	320	2,30	5150	1990	3160	640	670	5415
M 400/3.5	400	3,50	5810	2210	3600	900	780	6150
M 450/4.5	450	4,50	6745	2545	4200	900	910	7135
M 600/6	600	6,00	7265	2860	4405	1400	1140	7800
M 700/7.5	700	7,50	7850	3125	4725	1400	1250	7510
M 700/9	700	9,00	8550	3125	5425	1400	1250	8920
M 850/10.5	850	10,50	8695	3160	5535	1600	1480	8970
M 850/12	850	12,00	9530	3415	6115	1600	1480	10055
M 1000/16	1000	16,00	10200	3710	6490	1700	1625	11015
M 1000/20	1000	20,00	11610	3920	7690	1700	1625	12615
M 1300/25	1300	25,00	12135	4260	7875	2000	1950	12680
M 1400/32	1400	32,00	13635	4055	9580	2200	2080	14575
M 1700/40	1700	40,00	16749	5749	11000	2500	2450	16700